

## AZ3 HTE 2 Gravity Spray Gun

- **Fine finish polished body**  
Smooth polished surface makes it easier to clean
- **Ergonomic gun design**  
New trigger and ergonomic grip shape to relieve stress on painting
- **Light weight & well balanced body**  
Gun head 20-50 g lighter than previous model
- **New air flow valve**  
Increased control precision
- **Improved AKULON cup**  
Improved paint cup with multi thread construction
- **Pressure assisted cup (new product)**  
AirGunsa have added a pressure assisted paint cup system to the high viscosity paint application range
- **Spare parts compatible with previous AZ3 HTE**



Model	Ø mm	bar	l/min	ml/min	mm	No.	g	
AZ3 HTE 2	1.0	2.0	200	80	180	-	517	
	1.3			140	240	-		
	1.5			160	260	-		
	1.8	3.0	205	205	250	300		-
	2.0			300	340	-		
	2.5			279	450	360		-
	2.8			291	540	380		-
	3.0	288	560	400	-			
3.5	307	600	420	-				
AZ3 HTE HVLP	1.3	1.9	340	150	280	-		
	1.5			185	290	-		
	1.8			215	340	-		
	2.0			240	360	-		

Model	AZ3 HTE 2	
Test	Transfer Efficiency according to EN 13966-1	
Authority	IPA Fraunhofer Institut	
Date	27/03/2008	
Transfer efficiencies achieved with the materials detailed in the test report were:		
2K Primer Coat	89 %	
Water based Base Coat	79 %	
2K Clear Coat	84 %	
<small>Certification available on www.airgunsa.com</small>		

Max. Working Pressure: 6.8 bar (98 PSI)      Noise Level (LAeqT) 77.6 dB (A)  
 Temperature range: 5~40° C      Air nipple: G 1/4" M      Fluid nipple: G 1/4" F



declaration of ATEX conformity for use in zone 1 and in zone 2